

# AQUALAN

Designboden. Holz. Wasserbeständig.

**Design floor to click with Aqua Protect core board**



Technical Data	
Plank format	1.285 x 192 x 8 mm
Packaging unit	9 planks/2,22 m <sup>2</sup>
Palette content	52 cartons/115,46 m <sup>2</sup>
Wear layer	0,8 mm highly abrasion-resistant surface coating
Carrier board	7,2 mm Aqua Protect middle layer
Edge processing	circumferential V-gap
Laying method	drop down clic
Testing Values	
Abrasion resistance	AC 5
Resilient flooring classification (EN 649)	23/33
Determination of burning behaviour (EN 13501-1)	Bfl-s1 • Does not release toxic gas during combustio
Moisture proof	Yes
Stain resistance (EN 13329)	Level 5
Formaldehyde emission	Within the E1 standard
Suitable for underfloor heating	Yes
Slip retardant (EN 13893)	DS
Light fastness (EN 13329) blue scale	6
Residual indentation (EN 433)	≤ 0,05 mm
Impact resistance big ball	≥ 1000 mm
Suitable for caster chairs (EN 425)	Yes, with casters type W
Thermal conductivity (DIN-EN 12524)	0,073 m <sup>2</sup> x K/W
Disposal	Household waste

