

Mikolan

Mineral soils for clicking.



Technische Daten	Stone decor	Wood decor
Plank format	920 x 460 x 8,5 mm	1.235 x 200 x 8,5 mm
Packaging unit	4 planks/1,693 m ²	6 planks/1,482 m ²
Palette content	48 cartons/81,254 m ²	56 cartons/82,992 m ²
Surface	2-fold basic color application, digital printing, HotCoating PUR coating	
Top layer	1,0 mm High-density cork comfort top layer	
Carrier board	6,0 mm mineral plate	
Underlay	1,5 mm Green-Sound impact sound insulation	
Edge processing	4-sided super micro bevel	
Laying method	Glueless UNICLIC technique	
Testing Values		
Abraison resistance (EN 13329)	AC 5	
Resilient flooring classification (EN 16511)	23/33	
Determination of burning behaviour (EN 9239-1)	Cfl-s1 • Does not release toxic gas during combustion	
Resistance to chemicals (EN 423)	Very good resistance	
Moisture proof	Yes (fully glued)	
Mass per unit area (EN 430)	12.300 g/m ²	
Suitable for underfloor heating	Yes (hot water and electric underfloor heating)	
Light fastness (EN 185-B02)	7 / 8	
Dimensional stability and curling (EN 434)	< 0,01 %	
Residual indentation (EN 433)	< 0,20 mm	
Slip retardant (DIN 51130)	R 10	
Suitable for caster chairs (EN 425)	Yes, with casters type W	
Impact sound reduction (EN ISO 717-2)	19 dB	
Thermal conductivity (DIN-EN 12524)	0,08 m ² x K/W	
Resistance to stubbed and burning cigarettes	Yes	
Disposal	Household waste or Second Life	

