

Sombra Kork

Der lackierte Kork-Fertigfußboden.

Cork floor to click with HDF core board



Technical Data	
Plank format	915 x 305 x 11 mm
Packaging unit	6 planks/1,68 m ²
Palette content	60 cartons/100,80 m ²
Surface	HotCoating PUR coating or cream colored with HotCoating PUR coating
Top layer	3,0 mm natural cork
Carrier board	6,8 mm HDF
Underlay	1,2 mm Pressed cork impact sound insulation
Binder	Polyurethane
Edge processing	4-side flat
Laying method	Glueless UNICLIC technique
Testing Values	
Resilient flooring classification (EN 685)	23/32
Determination of burning behaviour (EN-4102)	Cfl-s1 • Does not release toxic gas during combustio
Moisture proof	No
Mass per unit area (EN 430)	7.400 g/m ²
Suitable for underfloor heating	Yes
Residual indentation (EN 433)	0,26 mm
Slip retardant (DIN 51130)	DIN = R 10
Suitable for caster chairs (EN 425)	Yes, with casters type W
Impact sound reduction (DIN 52210-030 E1-T-PFLD)	16 dB
Thermal conductivity (DIN-EN 52612-Teil 1)	0,088 m ² x K/W
Resistance to stubbed and burning cigarettes (EN 1933)	Yes
Disposal	Household waste or Second Life

