



Due to the long experience, GROUPE LAPROM offers beech lumber that meet your needs today and tomorrow. The timber range sold by us implies high quality raw materials and exceptional complementary services .

GROUPE LAPROM's competitive advantages are basically the high quality of the goods and the viable total cost for our customers.

This is due to the processing of performance management, but also long experience in international trading activity thereby developing sustainable business relationships with our partners throughout the value chain.

Only in this way we managed to establish lasting relationships and standing with clients in China, Malaysia, India, Pakistan, Saudi Arabia, North Africa (Algeria, Morocco and Libya) and South Africa.

Grade	Thickness (mm)	Width (mm)	Lenght (m)
A	25 - 80	100+	1.0 - 2.1+
		80+	0.3 - 0.95
B	25 - 80	100+	1.0 - 2.1+
		80+	0.3 - 0.95

Specification Beech destination China / Asia:

TIP	Grade	Thickness mm	Width mm	Length m
Beechwood	A	25;38;50;60;80;	100+	2,5+ (TAL S)
		25;38;50;60;80;	100+	2,1+ (TAL)
		25;38;50;60;80;	100+	1,8-2,0 (TAL1)
		25;38;50;60;80;	100+	1,0-1,7 (TAS)
		25;38;50;60;80;	80+	-0,3-95 (TASS)
	AB	25;38;50;60;80;	100+	2,5+ (TAL S)
		25;38;50;60;80;	100+	2,1+ (TAL)
		25;38;50;60;80;	100+	1,8-2,0 (TAL1)
		25;38;50;60;80;	100+	1,0-1,7 (TAS)
		25;38;50;60;80;	80+	0,3-0,95 (TASS)
	BC	25;38;50;60;80;	60+	2,5+ (TAL S)
		25;38;50;60;80;	60+	2,1+ (TAL)
		25;38;50;60;80;	60+	1,8-2,0(TAL1)
		25;38;50;60;80;	60+	1,0-1,7 (TAS)
		25;38;50;60;80;	60+	0,3-0,95 (TASS)

Standards that are supported:

- China 4FC (A grade)- 4 sides clear - is the highest class quality.The timber is clean, flawless (without knots and / or hearts).
- China 4FC (AB grade) - 4 sides clear - on one side of the piece of timber found traces of hearts healthy and / or a healthy node.
- China 3FC (BC grade) – 3 sides clear - allowed red heart, knots, bends and small cracks.

Lengths:

- 0.30 to 0.95 m timber sub-short (TASS)
- 1.00 to 1.70 m short timber (TAS)
- 1.80 to 2.00 m long timber (TAL)
- 2.10 to 3.00 m long super-timber (TAL +)

Heat treatment: Steaming light 10-12 hours, uniform color.

Drying: KD, KD 10-14% Markings: timber is packed with one length in the bundle and can have markings at customer request.

Specification Beech destination Middle East / North Africa:

TIP	Grade	Thickness mm	Width mm	Length m
Beechwood	A	25;27;38;50;60;80;	100+	2,1+ (TAL)
		25;27;38;50;60;80;	100+	1,8-2,0 (TAL1)
		25;27;38;50;60;80;	100+	1,0-1,7 (TAS)
		25;27;38;50;60;80;	80+	0,3-95 (TASS)
	B	25;27;38;50;60;80;	100+	2,1+ (TAL)
		25;27;38;50;60;80;	100+	1,8-2,0 (TAL1)
		25;27;38;50;60;80;	100+	1,0-1,7 (TAS)
		25;27;38;50;60;80;	80+	0,3-0,95 (TASS)

Accepted Standards

- Grade A - acceptance healthy heart, 3 and 4 faces clear
- Grade B - acceptance healthy heart, one or maxim two healthy knots per meter and with the maximum diammeter of the knot of 3 cm.

Lengths:

- 0.30 to 0.95 m timber Supershort (TASS)
- 1.00 to 1.70 m short timber (TAS)
- 1.80 to 4.00 m long timber (TAL)

Heat treatment: Steaming 12-24 hours, uniform color, drying, can be delivered fresh or dried (approx. 18%).

Markings: timber is packed with one length in the bundle and can have markings at customer request.